

Volatile Organic Compounds Gas Sensor

Product Data Sheet
Model #SB-4VOC-2000

2025. Ver 1.0

Applications & Features


- Ideal for portable and fixed gas detectors
- Industrial safety applications
- Emission monitoring
- Environmental air quality monitoring



Specifications

Performance Characteristics	
Output Signal	70±20 nA / ppm
Typical Baseline Range (pure air, @ 20°C)	≤ ±1 ppm iso-butylene equivalent
Response Time (T90)	< 30 seconds
Filter	None
Measurement Range	0-2000 ppm
Maximum Overload	4000 ppm
Linearity	Linear
Repeatability	< ±5% of signal
Recommended Load Resistor	10 ohms
Resolution (Electronics Dependent)	< 3 ppm typical
Bias Voltage	Not required
Environmental	
Temperature Range Continuous	-20°C to +50°C
Pressure Range	800 to 1200 mbar
Operating Humidity Range	15% to 90% RH
Lifetime	
Long Term Output Drift	< 5% per annum
Recommended Storage Temp	0°C to 20°C
Expected Operating Life	> 24 months in air
Standard Warranty	24 months from date of dispatch
Intrinsic Safety Data	
Maximum at 4000 ppm	0.4 mA
Maximum o/c Voltage	< 1.0 V
Maximum s/c Current	< 0.1 A

Dimension




Due to ongoing research and product improvement, specifications are subject to change without notice.

Volatile Organic Compounds Gas Sensor

Product Data Sheet
Model #SB-4VOC-2000

2025. Ver 1.0

Temperature Effects



Cross Sensitivity

Gas	Concentration [ppm]	Reading [ppm]
iso-Butylene	30	30
Acetylene	240	454
Ethylene	270	199
Ethane	240	22
Propylene	180	168
Vinyl Chloride	10	3
Acrylonitrile	20	2
Ethylene Oxide	10	1
Ethanol	210	50
Benzene	10	1
Methanol	50	3
Methane	1000	1
Isopropyl Alcohol	20	6
Tetrafluoromethane	2000	1
Fluoromethane	120	1
Difluoromethane	120	1
Carbon Monoxide	100	134
Hydrogen Sulfide	5	27
Chlorine	10	-4
Nitric Oxide	100	46
Nitrogen Dioxide	50	-47
Sulfur Dioxide	10	12
Hydrogen	500	160
Ammonia	100	0
Carbon Dioxide	5000	1


Due to ongoing research and product improvement, specifications are subject to change without notice.

Volatile Organic Compounds Gas Sensor

Product Data Sheet
Model #SB-4VOC-2000

2025. Ver 1.0

Standard Operating Circuit



Due to ongoing research and product improvement, specifications are subject to change without notice.